



UNI-Combigrip



UNI-Combigrip L PN10

Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating temperature EPDM: -30°C to 125°C
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton on request

Remark:

- For safe installation on PVC-, ABS-, PE-, PP- and PB-pipes insert stiffeners are mandatory

OD nominal (mm) (mm)	EPDM Code	SP	Weight (kg)	NBR Code
39.0 - 43.0	779 740 006	0	0.4	779 737 006
47.5 - 52.5	779 740 008	0	0.5	779 737 008
58.0 - 64.0	779 740 010	0	0.6	779 737 010
72.0 - 80.0	779 740 012	0	1.4	779 737 012
88.0 - 96.0	779 740 014	0	1.5	779 737 014
104.0 - 112.0	779 740 016	0	1.7	779 737 016
108.0 - 115.0	779 740 017	0	1.7	779 737 017
122.0 - 130.0	779 740 018	0	1.8	779 737 018
137.0 - 145.0	779 740 020	0	3.5	779 737 020
157.0 - 165.0	779 740 022	0	3.7	779 737 022
164.0 - 172.0	779 740 024	0	3.8	779 737 024

OD nominal (mm) (mm)	M	PN (bar)	WP (bar)	C max. (mm)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque (N/m)
39.0 - 43.0	M8	10	16	15	39.0	43.0	66	60	104	25
47.5 - 52.5	M8	10	16	15	47.5	52.5	74	60	112	25
58.0 - 64.0	M8	10	16	25	58.0	64.0	85	75	125	25
72.0 - 80.0	M10	10	16	30	72.0	80.0	108	95	164	40
88.0 - 96.0	M10	10	16	30	88.0	96.0	124	95	170	40
104.0 - 112.0	M10	10	16	30	104.0	112.0	141	95	187	40
108.0 - 115.0	M10	10	16	30	108.0	115.0	141	95	187	40
122.0 - 130.0	M10	10	16	30	122.0	130.0	158	95	202	40
137.0 - 145.0	M12	10	16	40	137.0	145.0	186	110	238	65
157.0 - 165.0	M12	10	16	40	157.0	165.0	205	110	255	65
164.0 - 172.0	M12	10	16	40	164.0	172.0	212	110	262	65